Prizefighter

Style and strength unite in the blue-ribbon enhanced resilient tile known as Prizefighter. This rigid core collection celebrates authentic wood visuals on a dimensionally stable and waterproof platform. Featuring an attached pad that offers superior acoustic properties, Prizefighter is ideal for a variety of applications, including guest rooms, corridors, and meeting spaces.

Prizefighter 831 One-Two, Color Balance 979 Magnetic
Cover: Prizefighter 747 Main Event

Prizefighter 959 Shadow Boxing, Color Balance 979 Magnetic

Color Balance COORDINATING CARPET TILE

New, visually intense Color Balance from Mohawk Group marries texture and color in a tufted plank rich with inspiration for modern installations. Global art, fashion and architecture have helped spark fresh interest in color blocking, multi-color hues and texture interplay. Color Balance's broad palette of 24 colorways gives designers endless options through color choice and texture orientation for accents or wall-to-wall installations. Use warm and cool neutrals balanced against vibrant accents for branding, way finding or indicating gradients. Color Balance is art underfoot.

FEATURES

- Construction: Tufted
- Fiber: Duracolor® Premium Nylon
- Colors available: 24
- Size: 12" x 36" (.3048m x .9144m)
- Stain Release Technology: Permanent, Built into the Fiber
- Soil Release Technology: EcoSentry Soil Protection
- Green Label Plus Certified #1171

Color Balance 556 Filtered, 839 Bone, 847 Sand, 945 Nickel, 949 Concrete, 979 Magnetic

Prizefighter 933 Off the Ropes, 888 Be First

Specifications

Prizefighter C0133

DESIGN

Overall Gauge	6.2mm
Wear Layer	20 mil
Finish	M-Force™ Enhanced Urethane
Colors Available	8
Size	
Nominal	7” x 48”
Actual	7.14” x 48.62”
Packaging	21.7 sq. ft. per carton / 9 pieces per carton / 44.01 lbs per carton
Installation	CLIC

PERFORMANCE

Construction	Rigid Enhanced Resilient Tile
Classification	ASTM F3261 - Grade 1, Type A - Smooth, Type B - Embossed
Squareness	ASTM F2055 - Passes - ±0.010” max
Size and Tolerance	ISO 24337 - Plank @ 48” - Passes - ±0.08”
Thickness, product	ASTM F387 - Passes - as specified ±0.005”
Thickness, wear layer	ASTM F410 - Passes - Commercial Min 0.02”
Dimensional Stability	ASTM F2199 - Passes - 0.020”/linear foot max
Curling	ASTM F2199 - Passes - 0.08” Max
Static Load Limit	ASTM F970 - Passes, modified at 1000 psi
Residual Indentation	ASTM F1914 - Passes - Average less than 0.007”
Resistance to Chemicals	ASTM F925 - Passes - No more than a slight change in surface dulling, surface attack, or staining
Resistance to Light	ASTM F1515 - Passes - $\Delta E < 8$
Resistance to Heat	ASTM F1514 - Passes - $\Delta E < 8$
Critical Radiant Flux	ASTM E648 - Class 1 (>0.45 W/cm2)
Smoke Density	ASTM E662 Part A - Less than 450

SUSTAINABILITY

Certification	FloorScore® Certified

*For detailed warranty, adhesive and installation information visit mohawkgroup.com

Mohawk Group

Mohawk Group
160 South Industrial Blvd.
Calhoun, GA. 30701
1-800-554-6637
mohawkgroup.com